

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: BC-Fertigtöne**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation Lacquer**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Further information obtainable from: Laboratory**
- **1.4 Emergency telephone number: +49(0)700 24112112 (MIP)**

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20: Harmful by inhalation.

R10-66: Flammable. Repeated exposure may cause skin dryness or cracking.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: BC-Fertigtöne

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning· **Hazard-determining components of labelling:**

n-butyl acetate
xylene

· **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition/information on ingredients· **3.2 Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	<i>n</i> -butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34	xylene ☠ Xn R20/21; ☠ Xi R38 R10 ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<12.5%

(Contd. on page 3)

Trade name: BC-Fertigtöne

(Contd. of page 2)

CAS: 78-93-3 EINECS: 201-159-0	butanone ☒ Xi R36; ☒ F R11 R66-67 ☒ Flam. Liq. 2, H225; ☒ Eye Irrit. 2, H319; STOT SE 3, H336	3-<10%
CAS: 100-41-4 EINECS: 202-849-4	Ethylbenzene ☒ Xn R20; ☒ F R11 ☒ Flam. Liq. 2, H225; ☒ Acute Tox. 4, H332	3-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 ☒ Flam. Liq. 3, H226	3-<10%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	butanol ☒ Xi R37/38-41 R10-67 ☒ Flam. Liq. 3, H226; ☒ Eye Dam. 1, H318; ☒ Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-<2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures· **4.1 Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Trade name: BC-Fertigtöne

(Contd. of page 3)

- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
- Use only in well ventilated areas.
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm
Long-term value: 154 mg/m³, 50 ppm

(Contd. on page 5)

Trade name: BC-Fertigtöne

(Contd. of page 4)

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· **Penetration time of glove material** Value for the permeation: Level ≤ 1

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

(Contd. on page 6)

Trade name: BC-Fertigtöne

(Contd. of page 5)

Boiling point/Boiling range:	108 °C
· Flash point:	30 °C (DIN 53213)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.0 Vol %
Upper:	7.6 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.977 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	135 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	69.4 %
VOC (EC)	678.4 g/l
Solids content (weight-%):	30.6 %
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral LD50 8700 mg/kg (rat)

(Contd. on page 7)

Trade name: BC-Fertigtöne

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|-----------|---|
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT, special provision 640E
- **IMDG, IATA** PAINT

(Contd. on page 8)

Trade name: BC-Fertigtöne

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Danger code (Kemler):** Warning: Flammable liquids.
30

· **EMS Number:** F-E,S-E

· **14.7 Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Transport category** 3
· **Tunnel restriction code** D/E
· **Remarks:** ≤ 450 l: -

· **IMDG**

· **Remarks:** ≤ 30 l: -

· **UN "Model Regulation":**

UN1263, PAINT, special provision 640E, 3, III

15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

Class	Share in %
NK	50-100

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Trade name: BC-Fertigtöne

(Contd. of page 8)

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H318 *Causes serious eye damage.*
- H319 *Causes serious eye irritation.*
- H332 *Harmful if inhaled.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H373 *May cause damage to organs through prolonged or repeated exposure.*

- R10 *Flammable.*
- R11 *Highly flammable.*
- R20 *Harmful by inhalation.*
- R20/21 *Harmful by inhalation and in contact with skin.*
- R36 *Irritating to eyes.*
- R37/38 *Irritating to respiratory system and skin.*
- R38 *Irritating to skin.*
- R41 *Risk of serious damage to eyes.*
- R66 *Repeated exposure may cause skin dryness or cracking.*
- R67 *Vapours may cause drowsiness and dizziness.*

· **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: *International Civil Aviation Organization*
- ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: *International Maritime Code for Dangerous Goods*
- IATA: *International Air Transport Association*
- GHS: *Globally Harmonized System of Classification and Labelling of Chemicals*
- EINECS: *European Inventory of Existing Commercial Chemical Substances*
- ELINCS: *European List of Notified Chemical Substances*
- CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
- VOC: *Volatile Organic Compounds (USA, EU)*
- LC50: *Lethal concentration, 50 percent*
- LD50: *Lethal dose, 50 percent*

· *** Data compared to the previous version altered.**