

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: BC-Verdünnung**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation** Thinner, Diluent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Further information obtainable from: Laboratory**
- **1.4 Emergency telephone number: +49(0)700 24112112 (MIP)**

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

R10-52/53-66-67: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

(Contd. on page 2)

Trade name: BC-Verdünnung

(Contd. of page 1)

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

n-butyl acetate

Solvent naphtha (petroleum), light arom.

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

*** 3 Composition/information on ingredients**

· **3.2 Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Trade name: BC-Verdünnung

(Contd. of page 2)

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	50-100%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Xn R65; ⚠ Xi R37; ⚠ N R51/53 R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	15-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34	xylene ⚠ Xn R20/21; ⚠ Xi R38 R10 ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H335	3-<10%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Xi R36; ⚠ F R11 R66-67 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H336	3-<10%
CAS: 100-41-4 EINECS: 202-849-4	Ethylbenzene ⚠ Xn R20; ⚠ F R11 ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H335	1-<2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures· **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

Trade name: BC-Verdünnung

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: *No special requirements.*

· Information about storage in one common storage facility: *Store away from foodstuffs.*

· Further information about storage conditions: *Keep container tightly sealed.*

· Storage class: 3

· 7.3 Specific end use(s) *No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical facilities: *No further data; see item 7.*

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

(Contd. on page 5)

Trade name: BC-Verdünnung

(Contd. of page 4)

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77 °C

(Contd. on page 6)

Trade name: BC-Verdünnung

(Contd. of page 5)

· Flash point:	21 °C (DIN 53213)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	97 hPa
· Density at 20 °C:	0.879 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	11 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	878.5 g/l
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

(Contd. on page 7)

Trade name: BC-Verdünnung

(Contd. of page 6)

1330-20-7 xylene

Oral	LD50	8700 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

14 06 03*	other solvents and solvent mixtures
-----------	-------------------------------------

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---------------------------------------|---|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR | 1263 PAINT RELATED MATERIAL, special provision 640D |
| · IMDG, IATA | PAINT RELATED MATERIAL |

(Contd. on page 8)

Trade name: BC-Verdünnung

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):** 33

· **EMS Number:** F-E,S-E

· **14.7 Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Transport category** 2

· **Tunnel restriction code** D/E

· **UN "Model Regulation":**

UN1263, PAINT RELATED MATERIAL, special provision 640D, 3, II

15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

Class	Share in %
NK	50-100

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 9)

Trade name: BC-Verdünnung

(Contd. of page 8)

- H304 *May be fatal if swallowed and enters airways.*
 H312 *Harmful in contact with skin.*
 H315 *Causes skin irritation.*
 H319 *Causes serious eye irritation.*
 H332 *Harmful if inhaled.*
 H335 *May cause respiratory irritation.*
 H336 *May cause drowsiness or dizziness.*
 H373 *May cause damage to organs through prolonged or repeated exposure.*
 H411 *Toxic to aquatic life with long lasting effects.*

- R10 *Flammable.*
 R11 *Highly flammable.*
 R20 *Harmful by inhalation.*
 R20/21 *Harmful by inhalation and in contact with skin.*
 R36 *Irritating to eyes.*
 R37 *Irritating to respiratory system.*
 R38 *Irritating to skin.*
 R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
 R65 *Harmful: may cause lung damage if swallowed.*
 R66 *Repeated exposure may cause skin dryness or cracking.*
 R67 *Vapours may cause drowsiness and dizziness.*

· **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
 ICAO: *International Civil Aviation Organization*
 ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
 IMDG: *International Maritime Code for Dangerous Goods*
 IATA: *International Air Transport Association*
 GHS: *Globally Harmonized System of Classification and Labelling of Chemicals*
 EINECS: *European Inventory of Existing Commercial Chemical Substances*
 ELINCS: *European List of Notified Chemical Substances*
 CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
 VOC: *Volatile Organic Compounds (USA, EU)*
 LC50: *Lethal concentration, 50 percent*
 LD50: *Lethal dose, 50 percent*

· *** Data compared to the previous version altered.**